

SPIT PULSA 27E



+ Pulsa E-Lift pole tool



In accordance to:
 EN 15895-1
 EN ISO 8662-11
 Directive tool :
 2012/19/EC
 2011/65/EC
 2006/42/EC
 2004/108/EC
 1999/5/EC
 Aerosol Dispenser Directive: 75/324/EC
 Battery:2006/66/EC
 Charger:2014/35/EU
 CEM 2014/30/EU

Tool Specifications

Name	SPIT PULSA 27E
Impact force (Joules)	95
Weight (kg)	3.4 kg (with battery)
Overall dimension LxH (mm)	345x112x315
Energy	Fuel cell & Battery
Fastener lengths (mm)	15 to 27 mm in strip

Characteristics

Electrical accessories pin-guide
Fully automatic tool (1000 shots per hour)
20 pins magazine (10 per strip)
Gas & Battery gauges: check gas & battery levels anytime
Start & Go system: energy saving, "self cut-off" when it is not used for 1mn
Low push down force (4.2 kg)
Automatic gas dosage (used T° - 15 °C to + 49 °C)
Battery charging time: 105 mn (25 mn = 1000 pins)
Fuel cell: 750 shots (20 °C), battery: up to 10000 shots
Depth of Drive button with 2 positions : DOD mini & DOD maxi
Bi-function hook 180° rotative : Belt and Scaffold positions

Safety Specifications

CE marking
Complete tool pressure necessary to generate the shot
Security with on / off led indicator
Noise level, EN 15895 : LpA,1s,1m=91.2dB(A) / Lp Cpeak=132.7 dB(C)
Vibration, EN ISO 8662-11: 4.9 m-s ⁻²

Accessories	Consumables
20 or 30 pins magazine WARNING: incompatible with Pulsa lift	C6, HC6, UP6, CG6,HCG6,CT-CLIP,E-CLIP,P-CLIP,CLIPLEC, Textile and Perforated strips,Tie-clip,Multiclip,Cable clasp,...
Magnetic pin guide	Metal P-CLIP, Metal Clip Elec ,MCC-O
Cleaning kit	
Pulsa E-Lift Pole Tool	